

XPRESS II STAIR LIFT

INCLINED PLATFORM LIFT FOR STRAIGHT STAIRWAYS



The Garaventa Stair-Lift Xpress II is an inclined platform lift designed for straight stairways. The Xpress II is a safe, reliable and cost-effective accessibility solution. This lift can be installed on your site with little to no structural modifications. It is suitable for public building and residential applications.

XPRESS II



Standard Features

- Large ADA compliant platform
- Choice of three platform sizes
- Passenger grab rail
- Under platform sensing plate and bi-directional ramp sensors
- Emergency manual lowering and folding system
- Ready lamp safety indicator
- Power-fold platform and ramps
- Keyed Call Stations
- Keyless platform for easier operation
- Platform controls include two large illuminated directional buttons and an emergency stop button
- Powered safety arms
- 2 year warranty

Optional Features

- Auxiliary power system
- Fire alarm integration
- Fold down seat with seat belt
- Side-load platform for installations with confined lower landings
- Attendant remote control
- Narrow platform sizes
- Platform folds automatically if left unattended at landing to keep stairways clear
- Keyed platform operation for added security
- Optional RAL colors
- Pedestrian audio visual alert
- Building fire alarm integration
- Vandal resistant platform lock (electric)
- Outdoor cover
- Extended warranty (5 additional years)
*USA/Canada only



The optional fold-down ambulatory seat allows a person with limited mobility to comfortably operate the Xpress II.

Specifications

Standard Platform Sizes:

800mm x 1250mm (31 1/2" x 49 1/4")
800mm x 1000mm (31 1/2" x 39 3/8")
750mm x 900mm (29 1/2" x 35 1/2")

Optional Platform Sizes:

675mm x 1000mm (26 1/2" x 39 3/8")
725mm x 1000mm (28 1/2" x 39 3/8")

Rated Load: 225 kg (495 lbs)

Speed:

Up: 4 meters (13 ft.) per minute
Down: 4.9 meters (16 ft.) per minute

Operating Controls:

Constant pressure switches, 24 VDC.

Drive System: Motor: 0.75 H.P.

Power Requirements: 208-240 VAC, 50/60 HZ single phase on a dedicated (North America = 20 amp, International = 15 amp) circuit.

Power Transmission: Rack & pinion

Emergency Use:

A handwheel is provided. Auxiliary power system available.

Rail System: Champagne anodized aluminum extrusion with integrally mounted zinc plated gear rack.

Overspeed Safety: Mechanical overspeed sensor and lock, with electrical drive cut-out protection.

Xpress Delivery Time: Standardized components allow us to provide custom configured lifts with very fast delivery times.

Free Inclined Platform Lifts DVD

Learn about how they work, key features, and the benefits offered. Available in DVD or VHS videotape formats. To order, contact your local dealer or visit our web site.

Free Design Assistance

Call your local Garaventa representative or our Design Hotline at: 1.800.663.6556

Architects

Many resources are available at www.garaventlift.com:

- Design Specifications
- Spec-Wizard
- CAD Blocks
- Design and Planning Guides
- Photo Gallery

Contact us today

Phone: +1 604 594-0422
Toll Free: 1 800 663 6556
Web site: www.garaventlift.com

Authorized Garaventa Lift Representative

15801-N-PB © Garaventa Lift. As we are continuously improving our products, specifications outlined in this brochure are subject to change without notice.

