

GENESIS VERTICAL LIFT

ENCLOSURE AND SHAFTWAY MODELS







For Lifting Heights Up To Fourteen Feet

The Garaventa Genesis is a vertical platform lift designed to provide access into or within public buildings. It travels inside a complete, self-contained enclosure, as shown, or can be located in a shaftway constructed by others. Our unique, anodized aluminum design is strong, durable and attractive.

Shaftway Model

The Genesis Shaftway model fits inside a vertical runway that is built by others in accordance to Garaventa Lift specifications. The system consists of a drive mast, passenger platform and doors or gates. The shaftway can be completely enclosed, much like an elevator shaftway, or it can be open at the upper landing. A variety of doors and gates are available.



The lower landing of this Genesis Shaftway model was designed with filler walls.

Applications:

Schools, churches, public buildings, clubs and residences

Standard Features


- Choice of Leadscrew or Continuous Mains Powered Hydraulic drive (with an auxiliary power system)
- Leadscrew drive for lifting heights up to 3734mm (147")
- Hydraulic drive for lifting heights up to 4343mm (171")
- Certified electric interlocks and automatic closer for doors and gates
- Sturdy 16 gauge galvanized steel platform side walls 1070mm (42 1/8") H
- Directional control switches and emergency stop switch
- Grab rail on platform side wall panel
- · Keyless operation
- Two year warranty


Optional Features


- Power Door Operators (ADA compliant)
- Custom platform sizes available
- Illuminated, tactile constant pressure directional buttons
- · Arrival gong and digital floor display
- Anodized aluminum doors/gates with Plexiglas panels or fire rated doors
- · Choice of RAL colors
- Autodialer phone (ADA compliant)
- Keyed operation
- Battery powered emergency lowering (Leadscrew drive only)
- Full time battery operation for low use applications (Hydraulic drive only)
- Custom applications (Consult Garaventa Lift)
- Extended warranty (five additional years) * USA/Canada only

Genesis Shaftway Dimensions (for more detailed information refer to the

(for more detailed information refer to the Genesis Design and Planning Guide)







	Shaftway Straight Through			
Platform	Shaftway	Shaftway	Platform	Platform
Size	Width	Length	Width	Length
Compact	1317mm	1295mm	914mm	1257mm
	[51 7/8"]	[51"]	[36"]	[49 1/2"]
Standard	1394mm	1407mm	992mm	1370mm
	[54 7/8"]	[55 3/8"]	[39"]	[53 7/8"]
Mid-Size	1394mm	1558mm	992mm	1520mm
	[54 7/8"]	[61 3/8"]	[39"]	[59 7/8"]
Large	1546mm	1558mm	1146mm	1520mm
	[60 7/8"]	[61 3/8"]	[45"]	[59 7/8"]

Shaftway 90° Entry/Exit				
Shaftway Width	Shaftway Length	Platform Width	Platform Length	
1272mm	1316mm	940mm	1208mm	
[50 1/8"]	[51 7/8"]	[37"]	[47 1/2"]	
1350mm	1428mm	1017mm	1320mm	
[53 1/8"]	[56 1/4"]	[40"]	[52"]	
1350mm	1579mm	1017mm	1471mm	
[53 1/8"]	[62 1/8"]	[40"]	[57 7/8"]	
1502mm	1579mm	1169mm	1471mm	
[59 1/8"]	[62 1/8"]	[46"]	[57 7/8"]	

Shaftway On/Off Same Side				
Shaftway Width	Shaftway Length	Platform Width	Platform Length	
1317mm	1316mm	914mm	1209mm	
[51 7/8"]	[51 7/8"]	[36"]	[49 1/2"]	
1394mm	1428mm	992mm	1320mm	
[54 7/8"]	[56 1/4"]	[39"]	[52"]	
1394mm	1579mm	992mm	1471mm	
[54 7/8"]	[62 1/8"]	[39"]	[57 7/8"]	
1546mm	1579mm	1144mm	1471mm	
[60 7/8"]	[62 1/8"]	[45"]	[57 7/8"]	

(Entry/Exit Adjacent to Mast)

- See separate drawings in the Genesis Design and Planning Guide for door details.
- Platform dimensions are clear inside dimensions.
- Ramp required for floor mount
- If the tie back rail (spreader bar) is to be used to attach the mast to the shaftway wall, the shaftway width dimension will increase by 38 mm [1 1/2"]
- Mast-to-wall attachment required

Enclosure Model


The Genesis Enclosure model is a complete, self-contained vertical access solution. It is similar to the Shaftway Model except it includes its own pre-fabricated enclosure and integrated doors or gates. The enclosure can be built full height and fitted with a Plexiglas dome for weather protection, or can be left open at the top.



This Enclosure model combines anodized aluminum extrusions with Plexiglas panels.

Genesis Enclosure Dimensions

(for more detailed technical information refer to the Genesis Design and Planning Guide)



	Enclosure Straight Through			
Platform Size	Base Width	Base Length	Platform Width	Platform Length
Standard	1399mm	1505mm	947mm	1370mm
	[55 1/8"]	[59 1/4"]	[37 1/4"]	[53 7/8"]
Mid-Size	1399mm	1656mm	947mm	1520mm
Wild-Size	[55 1/8"]	[65 1/8"]	[37 1/4"]	[59 7/8"]
Large	1551mm	1656mm	1099mm	1520mm
	[61 1/8"]	[65 1/8"]	[43 1/4"]	[59 7/8"]

Choice of Lead (with an auxili Leadscrew driv Hydraulic driv Interlocks and

Applications:


Schools, churches, public buildings, clubs and residences

Standard Features


- Choice of Leadscrew or Continuous Mains Powered Hydraulic drive (with an auxiliary power system)
- Leadscrew drive for lifting heights up to 3734mm (147")
- Hydraulic drive for lifting heights up to 4343mm (171")
- Interlocks and automatic closer for doors and gates
- Champagne colored anodized aluminum frame enclosure
- Sturdy 16 gauge galvanized steel platform side walls 1070mm (42 1/8") H
- Directional control switches and emergency stop switch
- Grab rail on platform side wall panel
- · Keyless operation
- Two year warranty

Optional Features

- Power Door Operators (ADA compliant)
- · Custom platform sizes available
- Illuminated and tactile constant pressure directional buttons
- Arrival gong and digital floor display
- Steel or Plexiglas enclosure panels
- Choice of RAL colors
- Autodialer phone (ADA compliant)
- Keyed operation
- Custom applications (Consult Garaventa Lift)
- Battery powered emergency lowering (Leadscrew drive only)
- Full time battery operation for low use applications (Hydraulic drive only)
- Fan and Ventilation System with thermostatic controls and battery backup
 requires Continuous Mains Power
- Extended warranty (five additional years) * USA/Canada only



E	Enclosure 90° Entry/Exit			
Base Width	Base Length	Platform Width	Platform Length	
1399mm [55 1/8"]	1505mm [59 1/4"]	1017mm [40"]	1295mm [51"]	
1399mm	1656mm	1017mm	1446mm	
[55 1/8"]	[65 1/8"]	[40"]	[56 7/8"]	
1551mm	1656mm	1155mm	1446mm	
[61 1/8"]	[65 1/8"]	[45 1/2"]	[56 7/8"]	



Enclosure On/Off Same Side				
Base Width	Base Length	Platform Width	Platform Length	
1399mm	1505mm	947mm	1295mm	
[55 1/8"]	[59 1/4"]	[37 1/4"]	[51"]	
1399mm	1656mm	947mm	1446mm	
[55 1/8"]	[65 1/8"]	[37 1/4"]	[56 7/8"]	
1551mm	1656mm	1099mm	1446mm	
[61 1/8"]	[65 1/8"]	[43 1/4"]	[56 7/8"]	

(Entry/Exit Adjacent to Mast)

- See separate drawings in the Genesis Design and Planning Guide for door details.
- Platform dimensions are clear inside dimensions.
- Ramp required for floor mount
- Mast-to-wall attachment required



GENESIS VERTICAL LIFT

Need Design Assistance?

Call your local Garaventa Lift representative or our Design Hotline at 1.800.663.6556

Leadscrew Drive

Platform Sizes

Enclosure Model Platforms: 947mm x 1370mm (37 1/4" x 54") 947mm x 1522mm (37 1/4" x 60") 1099mm x 1522mm (43 1/4" x 60")

Shaftway Model Platforms:

914mm x 1257mm (36" x 49 1/2") 992mm x 1370mm (39" x 54") 992mm x 1522mm (39" x 60") 1144mm x 1520mm (45" x 60")

Rated Load

340 kg (750 lbs), with a safety factor of 5

Speed

3 meters (10 ft) per minute at full load

Operating Controls

Keyless Controls: No key required for call stations and platform controls Directional Controls: Constant pressure switches Control Voltage: 24 VDC

Drive System

Motor:

2 HP (1750 RPM) Motor

Drive Type: ACME screw (1" diameter)

Mains Supply:

North American Models: 120 VAC on a dedicated 20 amp circuit International Models: 208-240 VAC on a dedicated 16 amp circuit

Hydraulic Drive

Platform Sizes

Enclosure Model Platforms: 947mm x 1370mm (37 1/4" x 54") 947mm x 1522mm (37 1/4" x 60") 1099mm x 1522mm (43 1/4" x 60")

Shaftway Model Platforms:

914mm x 1257mm (36" x 49 1/2") 992mm x 1370mm (39" x 54") 992mm x 1522mm (39" x 60") 1144mm x 1520mm (45" x 60")

Rated Load

340 kg (750 lbs), with a safety factor of 5

Speed

5.2 meters (17 ft) per minute at full load

Operating Controls

Keyless Controls: No key required for call stations and platform controls Directional Controls: Constant pressure switches Control Voltage: 24 VDC

Drive System

Motor:

3 HP (2.2 KW) Motor Drive Type: Chained Hydraulic

(Dual 5/8" ANSI 50 chains)

Mains Supply:

North American Models: 120 VAC on a dedicated 15 amp circuit International Models: 208-240 VAC on a dedicated 16 amp circuit



Architects

Many resources are available at www.garaventalift.com:

- · Design Specifications
- Spec-Wizard
- CAD Blocks
- Design and Planning Guides
- Photo Gallery

Contact us today

Phone: +1 604 594-0422
Toll Free: 1 800 663 6556
Web site: www.garaventalift.com

© Garaventa Lift. As we are continuously improving our products, specifications outlined in this brochure are subject to change without notice.

